

17 Series CX(E)A R410A cellar cooling

COMPETITIVE RANGE OF R410A CELLAR COOLERS BASED ON THE SAME HIGH SPECIFICATION INDOOR UNITS AS OUR SUCCESSFUL CX(E)/CKC RANGE

Features

- Revolutionary one piece molded body, impregnated with an anti-bacterial additive, ideal for cellar cooling and food preparation areas.
- Industrial standard 6 fins per inch evaporator coil.
- New 17 Series with smaller 5mm tube sizes in both the evaporator and condensing coils gives reduced refrigerant requirements without compromising the system duty.
- Condensing unit pre charged for up to 7.5m pipe run.
- Capacity range 2.3kW – 5.68kW @ 12.7°C
- Mounting brackets suitable for both wall and ceiling mounting.
- Up to 15m pipe run.

The Cellarator is available in 2 versions:

- CX ELECTROMECHANICAL (this unit has optional digital temperature display)
- CX(E) with electronic control

Lightweight indoor units for easy installation:-

CX(E) 30 - 18kg CX(E) 40 - 18kg
CX(E) 50 - 20kg CX(E) 70 - 23kg

The unit dimensions are:-

CX(E) 30 - 70 - 467mm x 845mm x 320mm



Specification

- New contemporary marble effect grey colour evaporator.
- Condensing units precharged with R410A
- The unit controls temperatures down to 4°C (dependent upon system match)
- De-ice stat is standard on CXE electronic units
- Antibacterial agent added to the chassis during the moulding process for complete mold protection throughout the material
- Waterproof power switch
- LP Switch
- 3 minute timer
- Random start contactor
- Direct access to the electrics at the front of the unit
- ABS drain tray incorporating standard 22mm OD fitting drain stub
- Easy to install field electric heater kit with factory fit option
- Outdoor condensing units incorporating a low pressure switch, HP switch and low ambient start as standard
- Optional ducted condensing units for where external installations are not feasible
- Air throws to suit all applications

Technical Information

Approximate Guide to Cellar Sizing in m³ at 27°C Ambient

SYSTEM	ABOVE GROUND		BELOW GROUND	
	CELLAR IN m ³		CELLAR IN m ³	
	8°C	12.7°C	8°C	12.7°C
CX(E)A 30 / CKA 35	20	26	25	31
CX(E)A 50 / CKA 35	25	30	31	39
CX(E)A 50 / CKA 50	30	42	46	57
CX(E)A 70 / CKA 70	40	55	61	75

Guide to Cooling Duty

SYSTEM	DUTY @ 12.7°C 27°C AMBIENT			DUTY @ 12.7°C 35°C AMBIENT			DUTY @ 8°C 27°C AMBIENT			DUTY @ 8°C 35°C AMBIENT			INTERCONNECTING PIPEWORK	
	TD (kW)	SD (kW)	INPUT (kW)	TD (kW)	SD (kW)	INPUT (kW)	TD (kW)	SD (kW)	INPUT (kW)	TD (kW)	SD (kW)	INPUT (kW)	SUCTION	LIQUID/ EXPANSION
CX(E)A 30 / CKA 35	2.28	1.98	1.17	2.20	1.77	1.30	1.79	1.69	1.15	1.73	1.20	1.25	1/2"	1/4"
CX(E)A 50 / CKA 35	3.25	2.48	1.19	2.83	2.15	1.25	3.06	2.36	1.15	2.66	1.80	1.25	1/2"	1/4"
CX(E)A 50 / CKA 50	4.25	2.90	1.62	3.50	2.45	1.60	3.44	2.40	1.51	2.83	2.00	1.50	1/2"	1/4"
CX(E)A 70 / CKA 70	5.60	3.83	2.31	4.62	3.24	2.46	4.54	3.17	2.16	3.74	2.60	2.30	5/8"	3/8"



CXA



CX(E)A



CKA Outdoor Unit

CX(E)A Indoor Unit

UNPACKED DIMENSIONS				
SYSTEM	HEIGHT mm	WIDTH mm	DEPTH mm	WEIGHT kg
CX(E)A 30	467	845	320	18
CX(E)A 50	467	845	320	20
CX(E)A 70	467	845	320	23

CKA Outdoor Unit

UNPACKED DIMENSIONS				
SYSTEM	HEIGHT mm	WIDTH mm	DEPTH mm	WEIGHT kg
CKA 35	552	760	256	34
CKA 50	552	760	256	42
CKA 70	660	860	307	56

We are the trusted partner for HVAC-R product solutions. Contact the specialists today for help and advice on your next project.

T: 01484 405 666
E: sales@marstair.com

TEV has earned management system accreditations – BSI 14001: 2015 Environmental Management and BSI 9001: 2015 Quality Management.



In partnership with

